


Exemplar™ Pull-Down Kitchen Faucet

- F-529-7EPC Finish(C)
- F-529-7EPGS Finish(GS)
- F-529-7EPSDB Finish(SDB)



Specifications

- TopPfit™ Installation
- MagnePfit™ Sprayhead Docking
- Pivot Sprayhead Technology

Features

- 1.8 GPM Flow Rate
- 1 or 3-Hole Installation; Deck Plate or Single Hole Mounting Option
- 3 Function Sprayer (Spray, Stream, and Pause)
- 360° Rotating High Arc Swivel Spout
- MagnePfit™ Sprayhead Docking
- TopPfit™ Top Mount Installation
- TopPfit™ Install Tool Included
- Pivot Sprayhead
- Mounting Hardware Included
- 3/8" Connection
- Spot Defense™ Finish Resists Spots and Fingerprints (GS & SDB Finish Only)
- 12.7 Extended Pull-Down Length
- Nylon Braided Hose
- Pfast Connect™ Adapter Technology
- Forward Handle Operation
- Integrated Flexible PE-RT Supply Lines
- TiteSeal™ Technology
- Pforever Seal™ Ceramic Disc Valve
- Limited Lifetime Warranty



Code Compliance

Pfister products are designed and manufactured in compliance with the following standards and codes:

- IAPMO Certified to ASME A112.18.1/CSA B125.1 including:
 - ASME A112.18.3 (Backflow Prevention)
- NSF/ANSI/CAN61:Q≤1
- CEC Certified/CALGreen compliant
- ADA Compliant - ANSI A117.1 (Lever Handle Only)



Dimensions

