


Highbury™ Pull-Down Kitchen Faucet

- LG529-HGC Finish(C)
- LG529-HGS Finish(S)
- LG529-HGY Finish(Y)



Specifications

Features

- 1.8 GPM Flow Rate
- 1-Hole Installation
- 3 Function Pull-Down Sprayer (Stream, Spray, and HydroBlade™)
- 13.5" Extended Hose Length
- Nylon Braided Hose
- 360° Rotating High Arc Spout
- AccuDock™ Sprayhead Docking
- Forward Handle Operation
- Pfast Connect™

- Optional Soap Pump Available, Order KSD-SRD* Separately
- Optional Deckplate Available, Order 961-221* Separately
- Convert to LEED Requirements with Separate Insert: Low Flow Regulator 1.5 GPM (941-683) and 1.0 GPM (941-444)
- Pforever Seal Ceramic Disc Valve
- Pforever Warranty®

Code Compliance

Pfister products are designed and manufactured in compliance with the following standards and codes:

- IAPMO Certified
- CSA B125 Certified
- ASME A112.18.1
- CAL Green Compliant
- CEC Compliant
- NSF 61/9 Annex G (Low lead)
- ADA Compliant-ANSI A117.1
- ASME A112.18.3 (Backflow Prevention)



Dimensions

