


- | | | |
|--|---|---|
| R89-1HVBG Finish(BG) <input type="checkbox"/> | LG89-7HVBG Finish(BG) <input type="checkbox"/> | LG89-8HVBG Finish(BG) <input type="checkbox"/> |
| R89-1HVC Finish(C) <input type="checkbox"/> | LG89-7HVC Finish(C) <input type="checkbox"/> | LG89-8HVC Finish(C) <input type="checkbox"/> |
| R89-1HVD Finish(D) <input type="checkbox"/> | LG89-7HVD Finish(D) <input type="checkbox"/> | LG89-8HVD Finish(D) <input type="checkbox"/> |
| R89-1HVGS Finish(GS) <input type="checkbox"/> | LG89-7HVGS Finish(GS) <input type="checkbox"/> | LG89-8HVGS Finish(GS) <input type="checkbox"/> |
| R89-1HVSD B Finish(SDB) <input type="checkbox"/> | LG89-7HVSD B Finish(SDB) <input type="checkbox"/> | LG89-8HVSD B Finish(SDB) <input type="checkbox"/> |



Specifications

Features

- 1.75 GPM Flow Rate
- Quick Connect Ball Joint Showerhead (1HV Excluded)
- Trim Only, Valve Not Included
- Requires OX8/JX8 Valve (Sold Separately)
- Valve Trim Only (1HV Only)
- Shower Only (7HV Only)
- Tub & Shower (8HV Only)
- Push Button Diverting Tub Spout with Removable Quick Connect Adapter (8HV Only)
- Spot Defense™ Finish Resists Spots and Fingerprints (GS & SDB Finish Only)
- Wipe Clean Nozzles
- Limited Lifetime Warranty



Code Compliance

Pfister products are designed and manufactured in compliance with the following standards and codes:

- IAPMO Certified to ASME A112.18.1/CSA B125.1
- CEC Certified/CALGreen compliant
- EPA WaterSense Certified
- ADA Compliant - ANSI A117.1 (Lever Handles Only)



Dimensions

