Highlights

- Complete Collection with Coordinating Roman Tub and Tub & Shower Options
- ¹/₄ Turn Ceramic Disc Valves
- Metal Lever Handles

Code Compliance

Price Pfister products are designed and manufactured in compliance with the following standards and codes:

- IAPMO certified • ASME A112.18.1
- CSA B125 certified ANSI A117.1 (Lever handles only)

49 Series ASHFIELD COLLECTION

8"-15" Widespread Faucet

Lever Handles

3-Hole Installation

1/4 Turn Ceramic Disc Valves

Finishes	T49-YP1C	T49-ΥΡ1Ε	749-YP1K	T49-YP1U	T49-YP1Y	T49-YP1Z
Rustic Bronze				Х		
Tuscan Bronze					Х	
Rustic Pewter		Х				
Polished Chrome	Х					
Oil Rubbed Bronze						х
Satin Nickel			Х			

Features	T49-YP1C	T49-YP1E	T49-YP1K	T49-YP1U	T49-YP1Y	T49-YP1Z
MatchMakers® Accessories Available	Х	Х	Х	Х	Х	Х
Solid Cast Brass Body and Spout	Х	Х	Х	Х	Х	Х
8"-15" Variable Installation	Х	Х	Х	Х	Х	Х
ADA Approved	Х	Х	Х	Х	Х	Х
Metal Pop-Up	Х	Х	Х	Х	Х	Х
Step-By-Step Installation Instructions	Х	Х	Х	Х	Х	Х
Pforever Warranty®	Х	Х	Х	Х	Х	Х



T49-YP1C T49-YP1Z

For additional information, please contact your Price Pfister representative, or visit our website at www.pricepfister.com.

Project: _

1-800-PFAUCET www.pricepfister.com 19701 DaVinci, Lake Forest, CA 92610 02/14/07

Price H (Pf) Pfreshest Ideas in Pfaucets.

Contractor: _

SS-049-16

Critical Dimensions:	
Minimum Hole Size	1 - 1 1/2 Dia Thru Hole 3 Places
Valve Centerline to Back Splash	2 3/8 Min

49 Series

ASHFIELD COLLECTION

8"-15" Widespread Faucet



CAUTION:



CAUTION: When using the compression fittings in this package, with these types of installations, the installer must flare or bead the water supply lines to avoid blow-out conditions. Avoiding such steps in the installation of the unit may result in water damage.

Connect inlet supply lines by assembling brass supply nut (A), friction ring (B) and cone washer (C) onto 3/8" O.D. straight copper tube. Bead or flare. Wrench tighten.

Dimensions are in Inches

1-800-PFAUCET www.pricepfister.com 19701 DaVinci, Lake Forest, CA 92610 02/1/07



SS-049-16