
PFISTER
FAUCETS

Pfirst Modern™

Pull-Down Kitchen Faucet

GT529-PFM2C Finish*(C)* ❑
GT529-PFM2S Finish*(S)* ❑
GT529-PFM2SDB Finish*(SDB)* ❑



- AutoDock™ Spray Head
- Forward Handle Operation
- Pforever Seal™

Specifications

Features


- 1.5 GPM Flow Rate
- 360º Rotating High Arc Spout
- 2 Function Pull-Down Sprayer (Spray and Stream)
- AutoDock™ Spray Head Docking
- 60" Braided Nylon Hose
- 12" Pull-Down Hose Length
- Forward Handle Operation
- Optional Deckplate Included
- 32" Integrated Nylon Braided Supply Lines with 3/8" Connections
- TiteSeal™ Technology
- Spot Defense™ Finish Resists Spots and Fingerprints (SDB Only)
- Pforever Seal™ Ceramic Disc Valve
- Limited Lifetime Warranty


Product Compliance

Pfister products are designed and manufactured in compliance with the following standards and codes:

- IAPMO Certified to ASME A112.18.1/CSA B125.1 including:
  - ASME A112.18.3 (Backflow Prevention)
- NSF/ANSI/CAN61:Q≤1
- CEC Certified/CALGreen compliant
- ADA Compliant – ANSI A117.1 (Lever Handle Only)

Dimensions





Optional Deckplate

Ø1-3/8 Min to Ø1-1/2 Max. Deck Hole Openings

1-800-PFAUCET (732-8238) • pfisterfaucets.com/support

Copyright © 2026, Pfister Faucets, an ASSA ABLOY Group company. All rights reserved.
Reproduction in whole or in part without the express permission of Pfister Faucets is prohibited.