


- |  |   |
|--|---|
| LF-049-VNBB Finish(BB) <input type="checkbox"/>  | LF-049-VNCC Finish(CC) <input type="checkbox"/> |
| LF-049-VNBBG Finish(BG) <input type="checkbox"/> | LF-049-VNGS Finish(GS) <input type="checkbox"/> |
|  | LF-049-VNYY Finish(YY) <input type="checkbox"/> |



## Specifications

### Features

- 1.2 GPM Flow Rate
- Adjustable 3-Hole Installation
- All Metal Construction
- Color Coded Connections
- High Arc Spout
- Fixed Hubs
- Mounting Hardware Included
- TiteSeal™ Technology
- Quick Install Tool Included
- Spot Defense Finish Resists Spots and Fingerprints (GS Finish Only)
- Pfaster Connect Supply Lines
- Push & Seal™ Pop-Up
- Pforever Seal Ceramic Disc Valves
- Pforever Warranty®

### Code Compliance

Pfister products are designed and manufactured in compliance with the following standards and codes:

- IAPMO Certified
- CSA B125 Certified
- ASME A112.18.1
- NSF 61/9 Annex G (Low lead)
- Cal Green Compliant
- CEC Compliant
- EPA WaterSense Certification 1.2 gpm, 4.5L/Min
- ADA Compliant-ANSI A117.1 (Lever handles only)



## Dimensions

