



- | | | |
|---|--|--|
| R89-1HTBG Finish(BG) <input type="checkbox"/> | LG89-7HTBG Finish(BG) <input type="checkbox"/> | LG89-8HTBG Finish(BG) <input type="checkbox"/> |
| R89-1HTC Finish(C) <input type="checkbox"/> | LG89-7HTC Finish(C) <input type="checkbox"/> | LG89-8HTC Finish(C) <input type="checkbox"/> |
| R89-1HTGS Finish(GS) <input type="checkbox"/> | LG89-7HTGS Finish(GS) <input type="checkbox"/> | LG89-8HTGS Finish(GS) <input type="checkbox"/> |
| R89-1HTSDB Finish(SDB) <input type="checkbox"/> | LG89-7HTSDB Finish(SDB) <input type="checkbox"/> | LG89-8HTSDB Finish(SDB) <input type="checkbox"/> |

Specifications

Features

- 1.75 GPM Flow Rate
- Quick Connect Ball Joint Showerhead (1HT Excluded)
- Trim Only, Valve Not Included
- Requires OX8/JX8 Valve (Sold Separately)
- Valve Trim Only (1HT Only)
- Shower Only (7HT Only)
- Tub & Shower (8HT Only)
- Quick Connect/SlipPfit Tub Spout (8HT Only)
- Spot Defense™ Finish Resists Spots and Fingerprints (GS & SDB Finish Only)
- Wipe Clean Nozzles
- Limited Lifetime Warranty



Code Compliance

Pfister products are designed and manufactured in compliance with the following standards and codes:

- IAPMO Certified to ASME A112.18.1/CSA B125.1
- CEC Certified/CALGreen compliant
- EPA WaterSense Certified
- ADA Compliant - ANSI A117.1 (Lever Handles Only)



Dimensions

