



- | | | |
|--|---|---|
| R89-1TNTC Finish(C) <input type="checkbox"/> | LG89-7TNTC Finish(C) <input type="checkbox"/> | LG89-8TNTC Finish(C) <input type="checkbox"/> |
| R89-1TNTK Finish(K) <input type="checkbox"/> | LG89-7TNTK Finish(K) <input type="checkbox"/> | LG89-8TNTK Finish(K) <input type="checkbox"/> |
| R89-1TNTB Finish(B) <input type="checkbox"/> | LG89-7TNTB Finish(B) <input type="checkbox"/> | LG89-8TNTB Finish(B) <input type="checkbox"/> |
| R89-1TNTBG Finish(BG) <input type="checkbox"/> | LG89-7TNTBG Finish(BG) <input type="checkbox"/> | LG89-8TNTBG Finish(BG) <input type="checkbox"/> |

Specifications

- SecurePfit™
- Trim Only, Valve Not Included

Features

- 1.8 GPM Flow Rate (Showerhead)
- All Metal Construction
- Metal Raincan Showerhead (8TNT Only)
- Brass Ball Joint (8TNT Only)
- SecurePfit™ with Anti-Handle Wobble
- Trim Only, Valve Not Included
- Easy to Clean Nozzles (8TNT Only)
- IP Threaded Diverted Spout (8TNT Only)
- Optional Crosshandle Available, Order HHL-089-TNT* Separately
- Hold/Cold Indicator
- Fits OX8/JX8 Valve Bodies
- Metal Lever Handle
- Must Order Pressure Balance Valve Separately
- Valve Trim Only (1TNT Only)
- Shower Only (7TNT Only)
- Tub & Shower (8TNT Only)
- Pforever Warranty®

Code Compliance

Pfister products are designed and manufactured in compliance with the following standards and codes:

- IAPMO Certified
- CSA B125 Certified
- ASME A112.18.1
- cUPC
- CEC Compliant
- Cal Green Compliant
- EPA WaterSense Certification 1.8 gpm, 6.8 L/Min
- ADA Compliant-ANSI A117.1 (Lever handles only)



Dimensions

